

KANALSKA

UNUTRAŠNJA JEDINICA

Kanalska unutrašnja jedinica predstavlja diskretno rješenje za prostore u kojima su estetika i skrivena ugradnja prioritet. Smještena iznad spuštenog plafona, omogućava ravnomjernu distribuciju vazduha uz minimalno vidljive elemente sistema, zbog čega je posebno pogodna za hotele, premium apartmane, kancelarije i savremene enterijere.



MODEL			ENYX PRIME DUCT IDU 9k WiFi R32	ENYX PRIME DUCT IDU 12k WiFi R32	ENYX PRIME DUCT IDU 18k WiFi R32
	Tip upravljanja		Daljinski upravljač	Daljinski upravljač	Daljinski upravljač
	Kapacitet hlađenja	Btu/h	9000	12000	18000
	Kapacitet grijanja	Btu/h	9500	13500	19600
	Pritisak	Visoki (DP)	MPa	3.7	3.7
		Niski (SP)	MPa	1.2	1.2
	Nivo zvučne snage (min/max)	dB(A)	55/37	55/37	56/38
	Nivo zvučnog pritiska (min/max)	dB(A)	43/27	43/27	46/28
	Električni podaci				
	Napajanje		220-240V~/50HZ	220-240V~/50HZ	220-240V~/50HZ
	Opseg napona	V	165~265	165~265	165~265
	Struja	Hlađenje	A	0.16	0.21
		Grijanje	A	0.16	0.21
	Power input	Hlađenje	W	35	48
		Grijanje	W	35	48
	Ventilatorski sistem				
	Protok vazduha	m3/h	600	600	850
	Izmjenjivač toplote				
	Broj redova	/	2	2	2
	Spoljašnji prečnik cijevi	mm	5	5	5
	Razmak lamela	mm	1.2	1.2	1.2
	Razmak cijevi (a) x razmak redova (b)	mm	19.5x11.6	19.5x11.6	19.5x11.6
	Povezivanje				
	Priključak rashladnog sredstva				
	Priključna cijev	Tečna faza	Inches	1/4"	1/4"
		Gasna faza	Inches	3/8"	3/8"
		Maksimalna dužina za svaku unutrašnju jedinicu	m	25m	25m
		Maksimalna visinska razlika	m	15m	15m
		Standardna dužina cjevovoda (fabričko punjenje)	g/m	5m/IDU	5m/iIDU
		Dodatno punjenje rashladnog sredstva	g/m	15g/m	15g/m
	Ostalo				
	Neto dimenzije (Š x V x D)	mm	700×490×200	700×490×200	920×490×200
	Neto težina	kg	15	15	18
	Dimenzije pakovanja (Š x V x D)	mm	900×555×250	900×555×250	1120×555×250
	Bruto težina	kg	18	18	21
	Eksterni statički pritisak (nominalni)	Pa	25	25	25
	Eksterni statički pritisak (opseg)	Pa	0-100	0-100	0-100
	Funkcionalnosti	WiFi upravljanje	Da	Da	Da